

SPECIFICATION SHEET
JFW MODEL 50FHC-XXX-15
FIXED ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range DC-4000 MHz (1-40 dB)
 DC-3000 MHz (41-60 dB)

Impedance 50 Ohms nominal

Attenuation Values 1-60 dB in any 1 dB increment
 (XXX) insert value

VSWR (1-40 dB) 1.15:1 maximum DC-1000 MHz
 1.35:1 maximum 1000-4000 MHz
 (41-60 dB) 1.15:1 maximum DC-1000 MHz
 1.35:1 maximum 1000-3000 MHz

Attenuation Accuracy (1-20 dB)
 ± 0.25 dB DC-1000 MHz
 ± 0.50 dB 1000-4000 MHz
 (21-30 dB)
 ± 0.50 dB DC-1000 MHz
 ± 0.75 dB 1000-4000 MHz
 (31-40 dB)
 ± 2% DC-2000 MHz
 ± 3% 2000-4000 MHz
 (41-60 dB)
 ± 2% DC-2000 MHz
 ± 3% 2000-3000 MHz

RF Input Power 15 Watts average
 Derate to 7.5 Watts @ +70°C

Peak Power 1000 Watts

RF Connector BNC, N, SMA, RPT, TNC, 4.1-9.5,
 4.3-10.0 or 7/16
 (RPT = reverse polarity TNC)

Operating Temperature Range -55°C to +100°C

Physical Size See outline drawing 092-1472

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
18344	03/03/2010	E	SMR 03/03/2010	26007	12/14/2015	H	CLK 12/14/2015
24263	06/23/2014	F	BAC 06/23/2014	26024	12/14/2015	I	TRS 12/14/2015
24660	10/29/2014	G	CLK 10/29/2014	27539	02/01/2017	J	CLK 02/01/2017

