



REV	ECN	DATE	BY	APPR
-	ISSUED	1-8-98	CDJ	PT
A	5856	10-27-98	PT	PT
B	5856	11-4-98	PT	PT
C	5860	11-9-98	TEZ	PT
D	5922	2-10-99	PT	PT
E	6989	1-29-02	CMB	TEZ
F	7508	6-13-03	BZ	TEZ
G	24444	9-10-19	GM	JZ



JFW INDUSTRIES, INC.

www.jfwindustries.com

PH: 317-887-1340

MATERIAL	BRASS	PROPRIETARY INFORMATION
FINISH	NICKEL	ALL SURFACES ARE TO BE FREE OF BURRS, PITS & SCRATCHES
MODEL	75BT-XXX F	TOLERANCES .XX±.010 .XXX±.005 XX°±.5°
DESCRIPTION	BIAS TAP	DWG # 092-2712

SPECIFICATION SHEET

JFW MODEL 75BT-007

BIAS TAP

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	100-1750 MHz
Impedance	75 Ohms nominal
VSWR	1.4:1 maximum 100-300 MHz 1.3:1 maximum 300-1750 MHz
Insertion Loss	1.25 dB maximum
DC Breakdown Voltage	200 Volts
DC Current Handling	2 Amps
RF Input Power	2 Watts average
RF Connector	BNC or F (male or female)
DC Connector	Solder Terminal (.040")
Operating Temperature Range	-55°C to +85°C
Physical Size	See outline drawings: 092-2712 (F female to F female) 092-5541 (F male to F female)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	01/13/1998			3078	08/09/2002	C	
1176	10/27/1998	A		9999	09/16/2002	D	SL 09/16/2002
1182	11/05/1998	B		20728	10/05/2011	E	TRS 10/05/2011